

SURFACE FINISHES COMPARISON CHART

PROPERTIES	ULTRALIT DENSIFIER	DRY SHAKE	EPOXY	CERAMIC TILES
Hardness level	Very hard (Mohs pencil >6)	Very hard (Mohs pencil >6)	Medium hardness	Very hard (Mohs pencil >6)
Abrasion resistance	Ultimate abrasion resistance, no scratches	High abrasion resistance	Easy scratching	High abrasion resistance, but very brittle, cracking close to joints
Sensitivity to moisture	Not sensitive	Not sensitive	Sensitive, can debond	Not sensitive
Stain resistance	Good resistance	Low resistance	High resistance	High resistance
Dusting	Dust free	Can generate dust	Dust free	Tiles are dust free, but cement joints dust
Floor is ready for use after	Typically 1 hour after application	Typically 7 days of curing is recommended	Typically 7 days of curing is recommended	Typically 7 days is recommended
Durability	Ultimate durability of over 15 years	In dependence of application quality, good durability of 5-8 years	Requires recoating every 2-4 years	Requires refurbishing every 3-5 years
Costs for maintenance	Easy cleaning, very low maintenance costs	Requires regular cleaning, medium maintenance costs	Regular cleaning, refurbishing, high maintenance costs	Regular cleaning, refurbishing, high maintenance costs
Cost of application per 1 m²	3-7 USD	4-7 USD	4-10 USD	6-15 USD
Cost of 1 m² during lifecycle	0.2-0.5 USD per year	0.8-0.9 USD per year	2-2.5 USD per year	2-3 USD per year